

SPECIFICATIONS

Central Air Conditioning

	GSX130181	GSX130241	GSX130301	GSX130361	GSX130421	GSX130481	GSX130601
Description	1.5 TON	2 TON	2.5 TON	3 TON	3.5 TON	4 TON	5 TON
SEER	Up to 13	Up to 13	Up to 13	Up to 13	Up to 13	Up to 13	Up to 13
Cooling Capacity (BTU/hr)	18,000	24,000	30,000	36,000	42,000	48,000	60,000
Manufacturer Compressor Limited Warranty	10 years	10 years	10 years	10 years	10 years	10 years	10 years
Width (in)	23	23	26	29	29	29	29
Depth (in)	23	23	26	29	29	29	29
Height (in)	23.75	25.75	27.5	28.75	36.25	36.25	40

Central Air Conditioning

	SSX140181	SSX140241	SSX140301	SSX140361	SSX140421	SSX140481	SSX140601
Description	1.5 TON	2 TON	2.5 TON	3 TON	3.5 TON	4 TON	5 TON
SEER	Up to 15	Up to 15	Up to 15	Up to 15	Up to 15	Up to 15	Up to 15
Cooling Capacity (BTU/hr)	18,000	24,000	30,000	36,000	42,000	48,000	60,000
Manufacturer Compressor Limited Warranty	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime
Width (in)	26	26	29	29	29	35.5	35.5
Depth (in)	26	26	29	29	29	35.5	35.5
Height (in)	27.5	32.5	32.5	34.25	38.25	36.25	38.25

Central Heat Pumps

	GSZ130181	GSZ130241	GSZ130301	GSZ130361	GSZ130421	GSZ130481	GSZ130601
Description	1.5 TON	2 TON	2.5 TON	3 TON	3.5 TON	4 TON	5 TON
SEER	Up to 14	Up to 14	Up to 14	Up to 14	Up to 14	Up to 14	Up to 14
Cooling Capacity (BTU/hr)	18,000	24,000	30,000	36,000	42,000	48,000	60,000
Manufacturer Compressor Limited Warranty	10 years	10 years	10 years	10 years	10 years	10 years	10 years
Width (in)	26	26	26	29	29	29	35.5
Depth (in)	26	26	26	29	29	29	35.5
Height (in)	32.25	32.25	32.25	32.25	38.25	34.25	34.25

Central Heat Pumps

	SSZ140181	SSZ140241	SSZ140301	SSZ140361	SSZ140421	SSZ140481	SSZ140601
Description	1.5 TON	2 TON	2.5 TON	3 TON	3.5 TON	4 TON	5 TON
SEER	Up to 15	Up to 15	Up to 15	Up to 15	Up to 15	Up to 15	Up to 15
Cooling Capacity (BTU/hr)	18,000	24,000	30,000	36,000	42,000	48,000	60,000
Manufacturer Compressor Limited Warranty	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime	Limited Lifetime
Width (in)	26	26	29	29	29	35.5	35.5
Depth (in)	26	26	29	29	29	35.5	35.5
Height (in)	27.5	32.5	32.5	34.25	38.25	38.25	38.25

Ductless Models with Inverter Feature

	NC15-09F	NC15-12F	NC15-16F	NC15-24F	NLS9F	NLS12F	NLS16F	NLS24F	NMH1-09F	NMH1-12F	NMH1-16F	NMH1-09F	NMH1-12F	NMH1-16F	NMH1-24F
Cooling Capacity (BTU/hr)	9,000	12,000	18,000	22,000	9,000	12,000	18,000	23,000	*9,000	*12,000	*18,000	9,000	12,000	18,000	24,000
Heating Capacity (BTU/hr)	-	-	-	-	10,700	13,000	18,900	24,600	*10,000	*13,000	*19,000	10,000	12,500	19,000	24,600
SEER	15	15	15	15	16	16.6	17.2	16	*16	*16	*16	19	18.8	19.2	18
HSPF	-	-	-	-	9.2	9	8.2	7.8	7.8	8.8	9.2	9.6	9.6	9.6	9.6
EER	9	9	9	9	12	12	12	9.6	12.4	12.1	12	14	12.5	12.5	12.5
Dehumidify (L/h)	1	1.2	1.8	2.4	1	1.2	1.8	2.6	1	1.2	1.8	1	1.2	1.8	2.6
Voltage	115/60	115/60	208-230/60	208-230/60	208-230/60	208-230/60	208-230/60	208-230/60	230/60	230/60	230/60	115/60	115/60	230/60	230/60
Refrigerant	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A	R-410A
Indoor Noise Level dB (A): H / M / L	39-35-28	39-35-29	42-39-31	49-45-39	40-36-30	44-41-39	50-45-42	50-48-46	37-32-27	37-32-27	42-37-34	39-35-32	39-38-37	48-44-42	51-48-45
Outdoor Noise Level (dB(A))	~56	~55	~59	~60	~55	~54	~59	~60	~60	~65	~65	~53	~55	~59	~59
Manufacturer Compressor Limited Warranty	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years	5 years
Maximum Pipe Length (ft./m)	66ft./20m	66ft./20m	82ft./25m	82ft./25m	65.6ft./20m	65.6ft./20m	82ft./25m	82ft./25m	† 82ft./25m	† 82ft./25m	† 82ft./25m	66ft./20m	66ft./20m	82ft./25m	82ft./25m
Maximum Elevation (ft./m)	26ft./8m	26ft./8m	33ft./10m	33ft./10m	26.2ft./8m	26.2ft./8m	32.8ft./10m	32.8ft./10m	† 49ft./15m	† 49ft./16m	† 49ft./17m	26ft./8m	26ft./8m	33ft./10m	33ft./10m
Refrigeration Pipe Diameter (Liquid side/ Gas side) (in)	.25/ .375	.25/ .5	.25/ .5	.375/ .625	.25/ .375	.25/ .5	.375/ .625	.375/ .625	.25/ .375	.25/ .375	.25/ .375	.25/ .375	.25/ .375	.25/ .375	.25/ .375

INDOOR DIMENSIONS

Width (in)	26.77	30.31	35.63	40.55	31.25	36.25	39.25	39.25	31.25	31.25	36.25	36.22	36.22	39.29	57.09
Depth (in)	7.01	7.4	7.8	8.58	7.25	8.75	9.5	9.5	7.75	7.75	8.75	8.78	8.78	9.45	10.43
Height (in)	10.04	10.04	10.83	12.4	10.5	11.5	12.75	12.75	10.5	10.5	11.5	11.5	11.5	12.68	13.39

OUTDOOR DIMENSIONS

Width (in)	26	26	29.92	33.27	30	30	33.25	33.25	33.27	33.27	38.98	29.92	29.92	33.27	35.43
Depth (in)	10.4	10.42	11.22	12.6	11.25	11.25	12.25	12.5	12.6	12.6	13.58	11.22	11.22	12.6	12.4
Height (in)	21.3	21.3	23.23	27.56	23.25	23.25	27.25	27.5	27.56	27.56	37.99	23.23	23.23	27.56	33.86

COMPARISON CHART

Remote control system	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Air filtration	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Improved efficiency	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Auto restart	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Turbo operation	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Sleep mode	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Auto swing	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Easy clean panel	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
PTC heating belt	-	-	-	-	•	•	•	•	•	•	•	•	•	•	•
DC inverter	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
LED display	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Low ambient cooling	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Louver position memory function	•	•	•	•	-	-	-	-	-	-	-	-	-	-	-
Refrigerant leakage detection	•	•	•	•	-	-	-	-	-	-	-	-	-	-	-
Energy Star rated	-	-	-	-	•	•	•	-	-	-	-	•	•	•	•

* Triple-zone units offer different indoor and outdoor models based on each room size and installation requirements. Please note BTU's and SEER ratings will change depending on the models selected.

† NMH1 Series states max. refrigerant pipe length for one indoor unit. See installation manual for specifications on installing multiple indoor units.