



CPS40

CPS40 PELLET STOVE (REAR VENT)

3" or 4" Pellet Vent

Unit includes: Concealed control panel, heat exchanger, black trivet, dual painted black accent rods, burn pot removal tool/rake, 120 CFM convection fan, pedestal with concealed ash pan, auto ignitor, air wash system, 55 lb hopper. 8,000 up to 43,000 BTU's. Suitable for mobile homes.

NOTE: DOOR MUST BE ORDERED TO COMPLETE UNIT			CDN.\$	
PRODUCT #	MODEL DESCRIPTION	FINISH	WT/lbs.	SUGG. LIST
CPS40	Pellet stove	painted black	202	\$2,459
DOORS				
GS328-1K	Door	painted black finish	14	\$395
GS328-1G	Door	gold plated (24 Karat)	14	\$599
GS328-1SS	Door	satin chrome plated	14	\$599
OPTIONS/A	CCESSORIES			
NP841KT	Decorative brick panels	sandstone	6	\$77
NPL41	Decorative log set		10	\$77
PRPP40	Porcelain reflective radiant panels		5	\$77
GS200-SS	Trivet	satin chrome plated	1	\$59
114KT	Outside air kit - 5 feet (2" dia.) with through the wall vent		2	\$59
NPHE40	Hopper extension (increases hopper capacity from 55 lbs to 80 lbs pellets)		8	\$129
209M	Paint, Stove Bright - metallic black 12 oz. MUST ORDER IN MULTIPLES OF 12		12	\$14

^{*} Note: For optimum performance, it is recommended that 4" diameter venting be utilized in high altitude regions (above 4,000 feet) or when vertical venting exceeds 15 feet.