







GVFT8 INDOOR VENT FREE TORCH

TESTED AS A HEATER TO THE UNVENTED HEATING STANDARD ANSI Z21.11.2

Unit includes: Exclusive energy saving "No Pilot" millivolt gas valve with oxygen depletion sensor (ODS), 2 on/off switches, one for burner and one for optional light kit, gas shut off, exclusive Torch™ burner with decorative glass embers, heat resistant glass and porcelain reflective panel. Bathroom/bedroom/bedsitting room and mobile home approved. 6,000 BTU's.

				US \$
PRODUCT #	MODEL DESCRIPTION	FINISH	WT/lbs.	SUGG. LIST
GVFT8N	Vent Free Torch™ gas fireplace	Natural gas	40	\$1,359
GVFT8P	П	Propane	40	\$1,359
MUST CHOO	SE ONE FRAME/FRONT & CABINET TO	COMPLETE UNIT (SEE OPTIONS ACCES. FO	R LIGHT KIT)	1
TFK	* Torch™ frame/front	painted metallic black finish	7	\$249
TFR	11 11	red finish	7	\$279
TFP	н н	pewter finish	7	\$279
TFW	п	white finish	7	\$279
TFB	II II	steel blue finish	7	\$279
TFSS	П	brushed stainless steel	7	\$379
TMCK	Adjustable mounting cabinet	painted metallic black finish	23	\$379
TMCSS	и и	brushed stainless steel	23	\$579
OPTIONS/AC	CCESSORIES			
LK8	Low voltage LED light kit (4) pre-wired for installation into TF kits		5	\$139
209M	Paint, Stove Bright - metallic black 12 oz. MUST ORDER IN MULTIPLES OF 12		12	\$14
10100-BULK	Stainless steel polish, case of 12		11	\$119

^{*} All frame/fronts are fabricated to accept optional light kit.

IMPORTANT: GVFT8 CANNOT BE RECESSED AND MUST BE INSTALLED IN CONJUNCTION WITH TMCK OR TMCSS (ADJUSTABLE MOUNTING CABINET) AND a TF_ (TORCH FRAME/FRONT)